



# WESPINE

INDUSTRIES  
PTY LTD

A.B.N. 88 052 954 337

Rev Date 26/06/09

---

## MATERIAL SAFETY DATA SHEET

### Non-treated Plantation Softwood

---

**IMPORTANT NOTICE:** This Material Safety Data Sheet (MSDS) is issued by WESPINE Industries Pty Ltd in accordance with WorkSafe Australia guidelines. As such, the information contained herein must not be altered, deleted or added to. WESPINE Industries Pty Ltd will issue a new MSDS when there is a change in either product specifications or WorkSafe Australia guidelines/regulations. WESPINE Industries Pty Ltd will not accept any responsibility for any changes made to its MSDS content by any other person or organisation.

---

### IDENTIFICATION

---

<b>Product Name:</b>	Non-chemically treated ["non-treated"] Plantation Softwood
<b>Chemical Name:</b>	Softwood
<b>UN Number:</b>	None allocated
<b>Trade Name:</b>	WESPINE
<b>Dangerous Goods Class:</b>	None allocated
<b>Subsidiary Risk:</b>	None allocated
<b>Hazchem Code:</b>	None allocated
<b>Poisons Schedule Number:</b>	Not scheduled
<b>Use:</b>	Non-treated plantation softwood has multiple uses including packaging, house framing, wall linings and furniture.

Head Office: Suite 12, 477 Orrong Road, Welshpool, Western Australia 6106

Telephone: (08) 9350 3900 Facsimile: (08) 9358 3137

Mill: 241 Moore Road, Dardanup, Western Australia 6236. P.O. Box 1320, Bunbury, Western Australia 6231

Telephone: (08) 9725 5777 Facsimile: (08) 9725 4559

Internet: [www.wespine.com.au](http://www.wespine.com.au)

## PHYSICAL DESCRIPTION/PROPERTIES

<b>Appearance:</b>	Non-treated seasoned plantation softwood has a blond colour prior to varnishing or other surface treatment. The product is sold as seasoned or green rough sawn, seasoned machined and moulded profiles.
<b>Odour:</b>	There is no odour
<b>Boiling Point:</b>	Not applicable
<b>Melting Point:</b>	Not applicable
<b>Vapour Pressure:</b>	Not applicable
<b>Flashpoint:</b>	Not applicable
<b>Flammability Limits in Air:</b>	Fine airborne dusts can ignite spontaneously
<b>Specific Gravity (water=1):</b>	Varies according to timber species and moisture content
<b>Molecular Weight:</b>	Not determined
<b>Solubility in Water:</b>	Highly insoluble
<b>pH (1% aqueous solution):</b>	Not applicable
<b>Auto-ignition Temperature:</b>	>220°C

## INGREDIENTS

<b>Chemical Entity:</b>	<b>CAS No.</b>	<b>Proportion (by weight):</b>
Softwood	none	>100%

## HEALTH HAZARD INFORMATION

**Health Effects:** The following health effects and recommendations refer to both non-treated green and non-treated seasoned plantation softwood.

Ensure non-treated green plantation softwood is stored and used in a well ventilated area. Storing and using this product in humid and poorly ventilated locations may produce an environment in which common air-borne mould spores can proliferate on the timber surface.

Handling wood may cause splinters.

### Acute Health Effects

**Swallowed:** Unlikely under normal conditions. Swallowing wood dust may cause abdominal discomfort.

**Eye:** Wood dust is irritating to the eyes resulting in redness and watering.

**Skin:** Skin contact with wood dust may result in skin irritation.

**Inhaled:** Inhalation of wood dust may be irritating to the nose, throat and lungs.

**Chronic Effects:** Repeated inhalation of dust from this product may increase the risk of nasal cavity cancer. Exposure to softwood and its dust in some susceptible people may result in respiratory and skin sensitisation leading to asthma and dermatitis respectively.

### First Aid

**Swallowed:** If swallowed, give water to drink. Seek medical attention if any abdominal discomfort.

**Eyes:** Flush thoroughly with water for at least 15 minutes. If irritation persists seek medical attention.

**Skin:** Wash thoroughly with mild soap and water. Remove clothing if contaminated with wood dust.

**Inhaled:** Leave the dusty area.

**Advice to Doctor:** Treat symptomatically.

## PRECAUTIONS FOR USE

**Exposure Standards:** WorkSafe Australia Exposure Standard for Wood dust (softwood).  
5mg/m<sup>3</sup> time weighted average (TWA) - measured as inspirable particulates.

10mg/m<sup>3</sup> short term exposure limit (STEL).

sen - sensitising to skin and respiratory tract.

Ensure non treated green plantation softwood is stored and used in a well ventilated area.

Keep exposures as low as practicable with the aim of maintaining inspirable wood dust levels below 1.0mg/m<sup>3</sup> TWA.

Head Office: Suite 12, 477 Orrong Road, Welshpool, Western Australia 6106

Telephone: (08) 9350 3900 Facsimile: (08) 9358 3137

Mill: 241 Moore Road, Dardanup, Western Australia 6236. P.O. Box 1320, Bunbury, Western Australia 6231

Telephone: (08) 9725 5777 Facsimile: (08) 9725 4559

Internet: [www.wespine.com.au](http://www.wespine.com.au)

## **WESPINE INDUSTRIES PTY LTD Recommendation:**

**Engineering Controls:** All work in plantation softwood must be carried out in such a way as to minimise exposure to wood dust. Under factory conditions, sawing, drilling or sanding of plantation softwood should be done with equipment fitted with local exhaust ventilation devices capable of removing dust at source.

**Respiratory Protection:** Avoid breathing sawdust from plantation pine. Wear a P1 or P2 respirator suitable for particulates and conforming to Australian Standards AS/NZS 1716 when exposed to dust.

Avoid disturbing mould growth on any green plantation softwood – allergic respiratory reactions may result.

**Skin Protection:** Wear industrial gloves (AS/NZS 2161), loose comfortable clothing [unless this will cause a hazard working in and around machinery] and boots. Long sleeved shirts and long trousers are recommended if skin irritation occurs. Wash skin with mild soap and water after working with plantation pine. Launder work clothes regularly and separately from other clothes. Wash hands well with soap and water before eating or smoking.

**Eye Protection:** Wear safety glasses or goggles, (AS/NZS 1336) if airborne dust is generated.

**Flammability:** Not flammable under normal conditions of use but is combustible and will help sustain a fire.

## **SAFE HANDLING INFORMATION**

**Storage and Transport:** Plantation softwood should be stored in a well-ventilated area away from sources of heat, flames and sparks.

No special transport requirements are considered necessary.

**Spills and Disposal:** Offcuts and general waste material should be placed in containers and disposed of at approved landfill sites or incinerated in accordance with local authority guidelines. Non-treated plantation softwood can be burnt in open fires, fireplaces and residential boilers.

**Fire/Explosion Hazard:** Dust may form an explosive mixture with air.

In a fire, use water jets to extinguish flames.

## **OTHER INFORMATION**

**Smoking:** WESPINE INDUSTRIES PTY LTD recommends that all storage and work areas should be smoking-free areas.

## **LABELLING REQUIREMENTS**

### **WARNING: PLANTATION SOFTWOOD**

- Risk:** Spores from mould growth on green plantation softwood stored in humid conditions may exacerbate respiratory conditions.
- Wood dust is irritating to eyes, skin and respiratory system. May cause sensitisation by inhalation (asthma) and skin contact (dermatitis). Repeated inhalation of wood dust may cause cancer.
- Safety:** Avoid prolonged exposure in humid conditions to green softwood exhibiting mould growth in restricted areas.
- Avoid repeated or prolonged contact with skin. Avoid contact with eyes. Avoid breathing dust. Wear suitable protective clothing including gloves (AS/NZS 2161), eye (AS/NZS 1336) and respiratory (AS/NZS 1716) protection if airborne dust generated, or if machining wood without adequate dust extraction.
- Wash work clothes regularly and separately from other clothes. Keep work areas clean by vacuuming or hosing and wet sweeping (not by compressed air or dry sweeping).
- First Aid:** If affected by dust irrigate eyes with plenty of water.
- Wash skin with soap and water.
- Disposal:** Follow above safety instructions and collect in containers for disposal as trade waste in accordance with local authority guidelines.
- Fire:** Wood dust can form an explosive mixture in air.
- Earth all exhaust equipment and prevent high dust concentrations in confined spaces.

## CONTACT POINT

**Further information may be obtained from:**

WESPINE INDUSTRIES PTY LTD

Head Office: Suite 12, 477 Orrong Road, Welshpool, Western Australia 6106

**Telephone: (08) 9350 3900 Facsimile: (08) 9358 3137**

Mill: 241 Moore Road, Dardanup, Western Australia 6236. P.O. Box 1320,  
Bunbury, Western Australia 6231

**Telephone: (08) 9725 5777 Facsimile: (08) 9725 4559**

Internet: [www.wespine.com.au](http://www.wespine.com.au)

**Emergency: Poisons Information Centre 13 11 26.**

---

While the information contained in this document is based on data that to the best of our knowledge was accurate and reliable at the time of preparation, we can accept no responsibility for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, we can accept no responsibility for any loss or damage caused by any person acting or refraining from action as a result of this information.

Head Office: Suite 12, 477 Orrong Road, Welshpool, Western Australia 6106

**Telephone: (08) 9350 3900 Facsimile: (08) 9358 3137**

Mill: 241 Moore Road, Dardanup, Western Australia 6236. P.O. Box 1320, Bunbury, Western Australia 6231

**Telephone: (08) 9725 5777 Facsimile: (08) 9725 4559**

Internet: [www.wespine.com.au](http://www.wespine.com.au)