

MATERIAL SAFETY DATA SHEET

IMPORTANT NOTICE: This Material Safety Data Sheet (MSDS) is issued by WESPINE INDUSTRIES PTY LTD in accordance with WorkSafe Australia guidelines. As such, the information contained herein must not be altered, deleted or added to. WESPINE INDUSTRIES PTY LTD will issue a new MSDS when there is a change in product specifications and/or WorkSafe Australia guidelines/regulations. WESPINE INDUSTRIES PTY LTD will not accept any responsibility for any changes made to its MSDS in content by any other person or organisation.

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Synonyms LOSP H3 TREATED PINE

1.2 Uses and uses advised against

Uses TIMBER
The product is timber used outdoors, but not in ground contact.

1.3 Details of the supplier of the product

Supplier name WESPINE INDUSTRIES PTY LTD
Address 241 Moore Road, Dardanup West, WA, 6236, AUSTRALIA
Telephone (08) 9725 5777
Fax (08) 9725 4559
Website <http://www.wespine.com.au/>

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

2.2 GHS Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
WOOD	-	-	>93%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	265-149-8	<10%
DIPROPYLENE GLYCOL METHYL ETHER	34590-94-8	252-104-2	<0.1%
PERMETHRIN	52645-53-1	258-067-9	<0.1%
PROPICONAZOLE	60207-90-1	262-104-4	<0.1%
TEBUCONAZOLE	107534-96-3	403-640-2	<0.1%
ZINC	7440-66-6	231-175-3	<0.1%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	<0.1%

Ingredient Notes The product may contain traces (<0.01%) of 3-Iodo-2-Propynyl Butylcarbamate (CAS 55406-53-6).

Wespine Industries Pty Ltd

Tel +61 8 9725 5777 PO Box 1320, 241 Moore Road,
Fax +61 8 9725 4559 Bunbury, WA, 6231 Dardanup, WA 6236

ABN 88 052 954 337

www.wespine.com.au

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye
Inhalation
Skin
Ingestion
First aid facilities

4.2 Most important symptoms and effects, both acute and delayed

No adverse health effects expected if the product is handled in accordance with the SDS and the product label.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Water spray or fog, for large quantities. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Finely divided dust may form explosive mixtures with air. May evolve metal oxides when heated to decomposition.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

If spilt, collect and reuse where possible.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a dry, well-ventilated area.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
2-(Methoxymethylethoxy) propanol	SWA [AUS]	50	308	--	--
Mineral Oil Mist	SWA [AUS]	--	5	--	--
Wood dust (certain hardwoods such as beech & oak)	SWA [AUS]	--	1	--	--
Wood dust (soft wood)	SWA [AUS]	--	5	--	10

Wespine Industries Pty Ltd

Tel +61 8 9725 5777 PO Box 1320, 241 Moore Road,
Fax +61 8 9725 4559 Bunbury, WA, 6231 Dardanup, WA 6236

ABN 88 052 954 337

www.wespine.com.au

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. If sanding, drilling or cutting, use appropriate local extraction ventilation. Maintain dust levels below the recommended exposure standard.

PPE

Eye / Face	Wear dust-proof goggles.
Hands	Wear leather or cotton gloves
Body	Not required under normal conditions of use.
Respiratory	If cutting or sanding with potential for dust generation, wear a Class P1 (Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	DRESSED OR NATURAL TIMBER
Odour	SLIGHT SOLVENT ODOUR
Flammability	COMBUSTIBLE
Flash point	NOT AVAILABLE
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Specific gravity	NOT AVAILABLE
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

Wespine Industries Pty Ltd

Tel +61 8 9725 5777

Fax +61 8 9725 4559

PO Box 1320,

Bunbury, WA, 6231

241 Moore Road,

Dardanup, WA 6236

ABN 88 052 954 337

www.wespine.com.au

10.5 Incompatible materials

Compatible with most commonly used materials.

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition. May evolve metal oxides when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity This product is expected to be of low toxicity. Based on available data, the classification criteria are not met.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	> 2000 mg/kg (rat)	> 2000 mg/kg (rabbit)	--
DIPROPYLENE GLYCOL METHYL ETHER	5.4 mL/kg (rat)	10 mL/kg (mouse)	--
PERMETHRIN	383 mg/kg (rat)	1750 mg/kg (rat)	485 mg/m ³ (rat)
PROPICONAZOLE	1517 mg/kg (rat)	> 4000 mg/kg (rat)	--
TEBUCONAZOLE	2000 mg/kg (mouse)	> 5000 mg/kg (rat)	> 800 mg/m ³ /4hrs (rat)

Skin	Not classified as a skin irritant. Prolonged or repeated exposure to dust may result in mechanical irritation and dermatitis.
Eye	Not classified as an eye irritant. Product may only present a hazard if wood is cut or sanded with dust generation, which may result in lacrimation and irritation.
Sensitisation	Not classified as causing skin or respiratory sensitisation.
Mutagenicity	Not classified as a mutagen.
Carcinogenicity	Not classified as a carcinogen. However, repeated exposure to wood dust may result in nasal and paranasal sinus cancers (IARC Group 1). Adverse health effects are usually associated with long-term exposure to high dust levels.
Reproductive	Not classified as a reproductive toxin.
STOT - single exposure	Not classified as causing organ damage from single exposure.
STOT - repeated exposure	Not classified as causing organ damage from repeated exposure.
Aspiration	Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Not expected to be harmful to aquatic life.

12.2 Persistence and degradability

Not applicable.

12.3 Bioaccumulative potential

This product does not bioaccumulate.

12.4 Mobility in soil

This product is immobile in soil.

12.5 Other adverse effects

No information provided.

Wespine Industries Pty Ltd

Tel +61 8 9725 5777

Fax +61 8 9725 4559

PO Box 1320,

Bunbury, WA, 6231

241 Moore Road,

Dardanup, WA 6236

ABN 88 052 954 337

www.wespine.com.au

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal	Dispose of to an approved landfill or waste processing site. Contact the manufacturer/supplier for additional information (if required).
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

Hazchem code None allocated.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule	Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.
Inventory listings	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information Do not burn treated timber. Do not use treated timber as mulch.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Wespine Industries Pty Ltd

Tel +61 8 9725 5777 PO Box 1320, 241 Moore Road,
Fax +61 8 9725 4559 Bunbury, WA, 6231 Dardanup, WA 6236

ABN 88 052 954 337

www.wespine.com.au

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmtglobal.com

[End of SDS]

Wespine Industries Pty Ltd

Tel +61 8 9725 5777 PO Box 1320, 241 Moore Road,
Fax +61 8 9725 4559 Bunbury, WA, 6231 Dardanup, WA 6236

ABN 88 052 954 337

www.wespine.com.au